



**ANSTRENGTH INJECTION MOLDING MACHINE
MODEL: AD130T-S219M**

INJECTION UNIT	MEASURE UNIT	MODELS		
DESCRIPTION	UNIT	AD130T-219M		
		A	B	C
Screw diameter	mm	32	36	40
Injection mass	g	124	156	193
Injection pressure	MPa	280	220	171
Plasticizing capacity	kg/h	53	76	101
Injection rate	cm ² /s	321	407	502
Injection distance	mm	160		
Injection speed	mm/s	400		
Rubber melting speed	rpm	400		
Nozzle protruding	mm	45		
Nozzle contact force	kN	45		
CLAMPING UNIT	MEASURE UNIT			
Clamping force	kN	1270(130)		
Plate dimension	mm x mm	720 x 670		
Mold thickness	mm	180-450		
Ejection force	kN	36(3.7)		
Ejection stroke	mm	100		
Pull-rod interval	mm x mm	510 x 460		
Opening stroke	mm	375		
OTHER MACHINE INFORMATION	MEASURE UNIT			
Equipment dimension	mm x mm x mm	5000 x 1250 x 1900		
Equipment weight	t	5.5		
Holding pressure	MPa	224	176	136

Please consult our sales representative or LOG-IMM before designing a mold.
 All specifications are based on theoretical conditions and subject to change without notice.
 Actual plasticizing capacity may vary depending on the molding conditions and material used.

LOG Injection Molding Machine 340 Commerce Drive, Crystal Lake, IL 60014
 847-648-6130 : Sales@LOG-IMM.com : www.log-imm.com