



**ANSTRENGTH INJECTION MOLDING MACHINE
MODEL: AD50T-S105M**

INJECTION UNIT		MEASURE UNIT		MODELS		
DESCRIPTION	UNIT	AD50T-S105M				
		A	B	C		
Screw diameter	mm	22	25	28		
Injection mass	g	38	49	61		
Injection pressure	MPa	285	221	180		
Plasticizing capacity	kg/h	18	26	37		
Injection rate	cm ² /s	190	245	308		
Injection distance	mm	104				
Injection speed	mm/s	500				
Rubber melting speed	rpm	400				
Nozzle protruding	mm	30				
Nozzle contact force	kN	12				
CLAMPING UNIT		MEASURE UNIT				
Clamping force	kN	490(50)				
Plate dimension	mm x mm	500 x 450				
Mold thickness	mm	160-350				
Ejection force	kN	21(2.1)				
Ejection stroke	mm	70				
Pull-rod interval	mm x mm	360 x 310				
Opening stroke	mm	250				
OTHER MACHINE INFORMATION		MEASURE UNIT				
Equipment dimension	mm x mm x mm	3650 x 990 x 1700				
Equipment weight	t	2.4				
Holding pressure	MPa	228	177	144		

Please consult our sales representative or LOG-IMM before designing a mold.
 All specifications are based on theoretical conditions and subject to change without notice.
 Actual plasticizing capacity may vary depending on the molding conditions and material used.

LOG Injection Molding Machine 340 Commerce Drive, Crystal Lake, IL 60014
 847-648-6130 : Sales@LOG-IMM.com : www.log-imm.com